



TABLE I

DASH NUMBER		TUBE O. D. NOM	A PIPE THREAD NPTF	B STRAIGHT THREAD CLASS 2A	D DIA DRILL	M ₁ ±.03	N ₁ ±.03	S ₂ MIN	Y ₁ ±.020
ASSY	*BODY								
1	21	1/8	1/8	5/16-24UNF	0.093	0.83	0.66	0.75	0.562
2	22	3/16	1/8	3/8-24UNF	0.125	0.83	0.66	0.76	0.562
3	23	1/4	1/8	7/16-20UNF	0.203	0.89	0.66	0.80	0.562
4	24	5/16	1/8	1/2-20UNF	0.234	0.95	0.66	0.82	0.562
5	25	3/8	1/4	9/16-18UNF	0.281	1.05	0.88	1.06	0.750
6	26	1/2	3/8	3/4-16UNF	0.422	1.23	1.02	1.27	0.875
7	27	5/8	1/2	7/8-14UNF	0.500	1.42	1.23	1.52	1.062
8	28	3/4	3/4	1-1/16-12UN	0.656	1.58	1.36	1.73	1.312
9	29	7/8	3/4	1-3/16-12UN	0.718	1.62	1.42	1.82	1.312
10	30	1	1	1-5/16-12UN	0.875	1.73	1.62	2.10	1.625
11	31	1-1/4	1-1/4	1-5/8-12UN	1.093	2.08	1.70	2.29	1.875
12	32	1-1/2	1-1/2	1-7/8-12UN	1.344	2.58	2.08	2.80	2.562
13	33	2	2	2-1/2-12UN	1.813	2.64	2.39	3.34	2.812

FOR NOTES SEE SHEET 2.

Ⓔ Denotes change

P.A. AR Other Cust 99	TITLE TEE, PIPE TO TUBE, FEMALE PIPE ON RUN, FLARELESS TYPE, HYDRAULIC	MILITARY STANDARD	
		MS51822	
PROCUREMENT SPECIFICATION MIL-F-18866	SUPERSEDES. CNHX13 in part and 13.1 in part	SHEET	1 OF 2

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document, when applicable.

Ⓔ

Review Activities:
Army - AF, GL, ME
Air Force - 82
DLA - CSUser Activities:
Army - AV
Navy - OS, MC

APPROVED 29 DEC 1967 REVISED 30 DEC 1970 22 NOV 1974 13 MAY 77 17 June 1982 30 July 1987

NOTES:

1. **MATERIAL:** Steel, carbon in accordance with procurement specification.
Steel, corrosion-resisting in accordance with procurement specification.
2. **PROTECTIVE COATING:** Cadmium plated in accordance with procurement specification.
Zinc plated in accordance with procurement specification.
Phosphate coating in accordance with procurement specification.
Passivation treatment in accordance with procurement specification.
3. **DIMENSIONS AND TOLERANCES:** Dimensions and tolerances not shown shall be in accordance with the SAE Standard for Flareless Tube Fittings (SAE J514).
4. **THREADS:** Threads shall be in accordance with Screw-Thread Standards for Federal Services, FED-STD-H28.
5. **PART NUMBER:** The MS part number consists of the MS number, plus the dash number and (for complete assembly) the applicable MS51825 sleeve style designator.
 - A. For the complete assembly (with nuts and sleeves), cadmium plated, use the MS number, plus the assembly dash number and the sleeve style designator.
Example: MS51822-1A or MS51822-1B.
 - B. For the body only, cadmium plated, use the MS number and the body dash number. Example: MS51822-21.
 - C. For zinc coating add "Z" and (for complete assembly) the sleeve style designator to the dash number. Example: MS51822-1ZA or MS51822-1ZB or MS51822-21Z.
 - D. For phosphate coating add "P" and (for complete assembly) the sleeve style designator to the dash number. Example: MS51822-1PA or MS51822-1PB or MS51822-21P.
 - E. For corrosion-resisting steel add "SS" and (for complete assembly) the sleeve style designator to the dash number. Example: MS51822-1SSA or MS51822-1SSB or MS51822-21SS.
6. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
7. Reference documents shall be of the issue in effect on date of invitations for bid.
8. The illustration is for identification and is not intended to restrict designs or shapes not dimensioned.
- * 9. After 22 NOV 1974, bodies will be used for production only and SHALL NOT be stocked for maintenance. Existing stock of bodies should be used until depleted.
10. CAUTION: The following data is furnished for the purpose of new design only and is not intended to imply interchangeability.

MS51822 will replace MS39209 for new design after approval date on this document. Table II below gives reference data for coordination of equivalent tube sizes, in both compression and hydraulic type tees. Assembly replacement is authorized.

TABLE II (FOR INFORMATION ONLY)
ASSEMBLY EQUIVALENCY

PART NUMBER		PART NUMBER		PART NUMBER	
COMPRESSION	HYDRAULIC	COMPRESSION	HYDRAULIC	COMPRESSION	HYDRAULIC
MS39209-1	MS51822-1	MS39209-5	MS51822-5	MS39209-9	MS51822-9
-2	-2	-6	-6	-10	-10
-3	-3	-7	-7	-11	-11
-4	-4	-8	-8	-12	-12

P.A. AR Other Cust 99	TITLE TEE, PIPE TO TUBE, FEMALE PIPE ON RUN, FLARELESS TYPE, HYDRAULIC	MILITARY STANDARD MS51822
PROCUREMENT SPECIFICATION MIL-F-18866	SUPERSEDES: CNHX13 in part and 13.1 in part	SHEET 2 OF 2

User Activities:
Army - AV
Navy - OS, MC

Review Activities:
Army - AT, CI, ME
Air Force - R2
DLA - CS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document, when applicable.

30 July 1987

17 June 1982

17

FOR CHANGES SEE SHEET 2

1

REVISED 30 DEC 1970

APPROVED 29 DEC 1967